


TG425


3-PHASE **WYE** DUAL STAGE POWER LINE FILTER

FEATURES

- » Rated currents include **15A, 30A, 50A, 80A, 100A, 150A, 200A, and 300A**
- » Dual Stage Line Filter
- » Available with **W** (wires), **S** (studs) and **C** (connectors) option
- » Agency Approved to UL1283 / 60929, CSA C22.2, EN 60939
- » Y-cap value can be adjusted to fit specification




ELECTRICAL SCHEMATIC



HOW TO ORDER

TG425- X - Y - Z



SPECIFICATIONS

OPERATING FREQUENCY	50/60Hz
USABLE FREQUENCY	DC - 400 Hz
MAX. OPERATING VOLTAGE	480V +10%
AMBIENT TEMPERATURE	-25 TO 50°C
CLIMATIC CATEGORY	25/100/21
TERMINALS (-T)	WIRE LEADS
	STUDS 15-50A (M5),
	80-100A (M6),
	150-200A(M10),
	300A(M12)
	CONNECTORS

TYP. WEIGHT, LBS (KG)	8.0 - 35.0 (3.6 - 15.9)
-----------------------	-------------------------

TYPICAL LEAKAGE CURRENT

@ 480 VAC 60 Hz	0 - 20.0 mA Max.
-----------------	------------------

HIPOT RATINGS

LINE TO GROUND	3500 VDC
----------------	----------

TYPICAL APPLICATIONS

- ✓ Power conversion systems
- ✓ Processing equipment
- ✓ Alternative energy equipment (EV charging & solar)
- ✓ Factory Machinery

TG425

3-PHASE **WYE** DUAL STAGE POWER LINE FILTER

MODEL NO.	RATED CURRENT, A @ 40° C	Y-CAP, nF	LEAKAGE CURRENT mA, @ 480V AC/60 Hz	TERMINAL OPTIONS			MAX. DIMENSIONS" (MM)		
				(W) INPUT/ OUTPUT	(S) INPUT/ OUTPUT	(C) INPUT/ OUTPUT	WIDTH	(LENGTH)	HEIGHT
TG425-15-0-S	15	0	-		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-15-0-W	15	0	-	✓			*	*	*
TG425-15-10-S	15	10	0.10		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-15-10-W	15	10	0.10	✓			*	*	*
TG425-15-100-S	15	100	1.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-15-100-W	15	100	1.00	✓			*	*	*
TG425-15-1000-S	15	1000	10.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-15-1000-W	15	1000	10.00	✓			*	*	*
TG425-15-2000-S	15	2000	20.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-15-2000-W	15	2000	20.00	✓			*	*	*
TG425-30-0-C	30	0	-			✓	*	*	*
TG425-30-0-S	30	0	-		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-30-0-W	30	0	-	✓			*	*	*
TG425-30-10-C	30	10	0.10			✓	*	*	*
TG425-30-10-S	30	10	0.10		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-30-10-W	30	10	0.10	✓			*	*	*
TG425-30-100-C	30	100	1.00			✓	*	*	*
TG425-30-100-S	30	100	1.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-30-100-W	30	100	1.00	✓			*	*	*
TG425-30-1000-C	30	1000	10.00			✓	*	*	*
TG425-30-1000-S	30	1000	10.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-30-1000-W	30	1000	10.00	✓			*	*	*
TG425-30-2000-C	30	2000	20.00			✓	*	*	*
TG425-30-2000-S	30	2000	20.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-30-2000-W	30	2000	20.00	✓			*	*	*
TG425-50-0-C	50	0	-			✓	*	*	*
TG425-50-0-S	50	0	-		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-50-0-W	50	0	-	✓			*	*	*
TG425-50-10-C	50	10	0.10			✓	*	*	*
TG425-50-10-S	50	10	0.10		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-50-10-W	50	10	0.10	✓			*	*	*
TG425-50-100-C	50	100	1.00			✓	*	*	*
TG425-50-100-S	50	100	1.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-50-100-W	50	100	1.00	✓			*	*	*

TG425

3-PHASE **WYE** DUAL STAGE POWER LINE FILTER

MODEL NO.	RATED CURRENT, A @ 40° C	Y-CAP, nF	LEAKAGE CURRENT mA, @ 480V AC/60 Hz	TERMINAL OPTIONS			MAX. DIMENSIONS" (MM)		
				(W) INPUT/OUTPUT	(S) INPUT/OUTPUT	(C) INPUT/OUTPUT	WIDTH	(LENGTH)	HEIGHT
TG425-50-1000-C	50	1000	10.00			✓	*	*	*
TG425-50-1000-S	50	1000	10.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-50-1000-W	50	1000	10.00	✓			*	*	*
TG425-50-2000-C	50	2000	20.00			✓	*	*	*
TG425-50-2000-S	50	2000	20.00		✓		3.50"(89)	10.00"(254)	2.75"(70)
TG425-50-2000-W	50	2000	20.00	✓			*	*	*
TG425-80-0-C	80	0	-			✓	*	*	*
TG425-80-0-S	80	0	-		✓		3.90"(99)	12.36"(314)	3.25"(83)
TG425-80-0-W	80	0	-	✓			*	*	*
TG425-80-10-C	80	10	0.10			✓	*	*	*
TG425-80-10-S	80	10	0.10		✓		3.90"(99)	12.36"(314)	3.25"(83)
TG425-80-10-W	80	10	0.10	✓			*	*	*
TG425-80-100-C	80	100	1.00			✓	*	*	*
TG425-80-100-S	80	100	1.00		✓		3.90"(99)	12.36"(314)	3.25"(83)
TG425-80-100-W	80	100	1.00	✓			*	*	*
TG425-80-1000-C	80	1000	10.00			✓	*	*	*
TG425-80-1000-S	80	1000	10.00		✓		3.90"(99)	12.36"(314)	3.25"(83)
TG425-80-1000-W	80	1000	10.00	✓			*	*	*
TG425-80-2000-C	80	2000	20.00			✓	*	*	*
TG425-80-2000-S	80	2000	20.00		✓		3.90"(99)	12.36"(314)	3.25"(83)
TG425-80-2000-W	80	2000	20.00	✓			*	*	*
TG425-100-0-C	100	0	-			✓	*	*	*
TG425-100-0-S	100	0	-		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-100-0-W	100	0	-	✓			*	*	*
TG425-100-10-C	100	10	0.10			✓	*	*	*
TG425-100-10-S	100	10	0.10		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-100-10-W	100	10	0.10	✓			*	*	*
TG425-100-100-C	100	100	1.00			✓	*	*	*
TG425-100-100-S	100	100	1.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-100-100-W	100	100	1.00	✓			*	*	*
TG425-100-1000-C	100	1000	10.00			✓	*	*	*
TG425-100-1000-S	100	1000	10.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-100-1000-W	100	1000	10.00	✓			*	*	*
TG425-100-2000-C	100	2000	20.00			✓	*	*	*

TG425

3-PHASE **WYE** DUAL STAGE POWER LINE FILTER

MODEL NO.	RATED CURRENT, A @ 40° C	Y-CAP, nF	LEAKAGE CURRENT mA, @ 480V AC/60 Hz	TERMINAL OPTIONS			MAX. DIMENSIONS" (MM)		
				(W) INPUT/ OUTPUT	(S) INPUT/ OUTPUT	(C) INPUT/ OUTPUT	WIDTH	(LENGTH)	HEIGHT
TG425-100-2000-S	100	2000	20.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-100-2000-W	100	2000	20.00	✓			*	*	*
TG425-150-0-C	150	0	-			✓	*	*	*
TG425-150-0-S	150	0	-		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-150-0-W	150	0	-	✓			*	*	*
TG425-150-10-C	150	10	0.10			✓	*	*	*
TG425-150-10-S	150	10	0.10		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-150-10-W	150	10	0.10	✓			*	*	*
TG425-150-100-C	150	100	1.00			✓	*	*	*
TG425-150-100-S	150	100	1.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-150-100-W	150	100	1.00	✓			*	*	*
TG425-150-1000-C	150	1000	10.00			✓	*	*	*
TG425-150-1000-S	150	1000	10.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-150-1000-W	150	1000	10.00	✓			*	*	*
TG425-150-2000-C	150	2000	20.00			✓	*	*	*
TG425-150-2000-S	150	2000	20.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-150-2000-W	150	2000	20.00	✓			*	*	*
TG425-200-0-C	200	0	-			✓	*	*	*
TG425-200-0-S	200	0	-		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-200-0-W	200	0	-	✓			*	*	*
TG425-200-10-C	200	10	0.10			✓	*	*	*
TG425-200-10-S	200	10	0.10		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-200-10-W	200	10	0.10	✓			*	*	*
TG425-200-100-C	200	100	1.00			✓	*	*	*
TG425-200-100-S	200	100	1.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-200-100-W	200	100	1.00	✓			*	*	*
TG425-200-1000-C	200	1000	10.00			✓	*	*	*
TG425-200-1000-S	200	1000	10.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-200-1000-W	200	1000	10.00	✓			*	*	*
TG425-200-2000-C	200	2000	20.00			✓	*	*	*
TG425-200-2000-S	200	2000	20.00		✓		6.60"(168)	16.02"(407)	4.50"(114)
TG425-200-2000-W	200	2000	20.00	✓			*	*	*
TG425-300-0-S	300	0	-		✓		7.00"(178)	21.53"(547)	5.00"(127)
TG425-300-10-S	300	10	0.10		✓		7.00"(178)	21.53"(547)	5.00"(127)


TG425

3-PHASE **WYE** DUAL STAGE POWER LINE FILTER

MODEL NO.	RATED CURRENT, A @ 40° C	Y-CAP, nF	LEAKAGE CURRENT mA, @ 480V AC/60 Hz	TERMINAL OPTIONS			MAX. DIMENSIONS" (MM)		
				(W) INPUT/ OUTPUT	(S) INPUT/ OUTPUT	(C) INPUT/ OUTPUT	WIDTH	(LENGTH)	HEIGHT
TG425-300-100-S	300	100	1.00		✓		7.00"(178)	21.53"(547)	5.00"(127)
TG425-300-1000-S	300	1000	10.00		✓		7.00"(178)	21.53"(547)	5.00"(127)
TG425-300-2000-S	300	2000	20.00		✓		7.00"(178)	21.53"(547)	5.00"(127)

*Contact factory for dimensions.

TG425 MECHANICAL OUTLINES (MM)



SERIES	(A)	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
STUDS (15/30/50A)	10.00" (254)	3.50" (89)	2.75" (70)	9.00" (229)	8.00" (203)	3.50" (89)	2.55" (65)	0.48" (12)	1.75" (45)	2.00" (51)	0.75" (19)	Ø 0.48x0.25", 4x (Ø 12.2x6.5, 4x)	STUD M5, 8x	STUD, GND, M5	0.50" (13)	2.50" (64)	0.50" (13)
STUDS (80A)	12.36" (314)	3.90" (99)	3.25" (83)	11.00" (279)	10.00" (254)	4.00" (102)	2.69" (68)	0.65" (17)	2.00" (51)	2.25" (57)	1.00" (25)	Ø 0.5x0.25" 4x (Ø 12.7x6.4, 4x)	STUD, M6, 8x	STUD, GND, M6	0.50" (13)	3.00" (76)	0.45" (11)
STUDS (100/150/200A)	16.02" (407)	6.60" (168)	4.50" (114)	14.69" (373)	13.00" (330)	6.60" (168)	4.60" (117)	1.00" (25)	3.30" (84)	3.50" (89)	1.00" (25)	Ø 0.59x0.29", 4x (Ø 15.2x7.6, 4x)	STUD M10, 8x	STUD, GND, M10	0.53" (14)	5.12" (130)	0.64" (16)
STUDS (300A)	21.53" (547)	7.00" (178)	5.00" (127)	19.00" (483)	18.00" (457)	7.00" (178)	4.80" (122)	1.10" (26)	3.50" (89)	4.00" (102)	1.00" (25)	Ø 0.59x0.29", 4x (Ø 15.2x7.6, 4x)	STUD M12, 8x	STUD, GND, M12	0.50" (13)	6.00" (152)	0.50" (13)

TYPICAL TOLERANCE: +/-0.02" (0.50MM)

TG425

3-PHASE **WYE** DUAL STAGE POWER LINE FILTER

TYPICAL INSERTION LOSS, dB (50/50 Ohm)

Amps	Freq (MHz)	0.15	0.5	1.0	10	30
15	CM (dB)	65	75	75	58	40
	DM (dB)	65	75	75	75	70
30	CM (dB)	65	75	75	58	40
	DM (dB)	65	75	75	75	70
50	CM (dB)	58	70	70	58	40
	DM (dB)	60	70	75	70	60
80	CM (dB)	54	65	65	55	40
	DM (dB)	55	60	60	50	38
100	CM (dB)	70	75	75	58	30
	DM (dB)	55	70	70	60	30
150	CM (dB)	65	70	70	55	30
	DM (dB)	50	65	70	60	30
200	CM (dB)	60	65	60	50	35
	DM (dB)	55	60	65	60	30
300	CM (dB)	60	65	60	48	40
	DM (dB)	55	55	55	50	30