



SL-AC Series Powder Coated, Manual Timer, Two Taps, Landscape, Low Voltage Series Landscape low voltage lighting transformer specifically designed for LED landscape fixtures. The transformer has two output options 12V and 15V for either a short and long distance circuits to compensate wire drop voltage. High grade core and copper winding provide excellent load regulation and efficiency. Build in manual 24h timer and photocell provide full control and energy savings. Secondary push to reset circuit breaker provide short circuit and overload protection. Removable slide door. Suitable for Wet Location, ETL Listed to UL STD 1838, CSA STD C22.2 250.0 and 250.7

Max Output Power:75- 600W

Max Output Current: 12.5A/15V

Max Output Voltage: 14VAC/17.5V

Output Terminals: 2

Input Voltage Rating: 120VAC

IP Rating: IP 21

Exterior Construction: Anodized Aluminum

Landscape Transformers SL-AC Series-Slide Series Specification

Model No.	Wattage	Input Voltage	Output Voltage	Terminal Block	Secondary Breaker	Num. of circuits
SL75WS	75W	120V 60Hz	12VAC or 15VAC	√	√	single
SL100WS	100W	120V 60Hz	12VAC or 15VAC	√	√	single
SL150WS	150W	120V 60Hz	12VAC or 15VAC	√	√	single
SL200WS	200W	120V 60Hz	12VAC or 15VAC	√	√	single
SL300WS	300W	120V 60Hz	12VAC or 15VAC	√	√	single
SL600WS	600W	120V 60Hz	12VAC or 15VAC	√	√	single