



Outline:

- 18.5 x 14mm Typ.(L x W),6.70mm Typ.Height
- Carrier tape packing, suitable for SMT process
- Low DCR and excellent current handling
- Magnetically shielded construction
- In addition to the standard versions of inductors shown here custom inductors are available to meet your exact requirements

Features:

- Core material:Ferrite
- Environmental: RoHS, Reach compliant ,Halogen free
- Weight:3.37g
- Moisture Sensitivity:Level (MSL) 1
(unlimited floor life at <30°C / 85% relative humidity).
- Operating temperature range: -40°C~+125°C
(including coil's self temperature rise)
- Storage temperature range: -40°C~+125°C


Application:

- Ideally used in Notebook PC,LCD T,Game machine STB
- buck converter,network communication equipment, and etc

1 Electrical Characteristics

Part No.	Inductance (μH) $\times 1$ $\pm 20\%$	D.C.R. (m Ω)		Isat	Irms
		Typical	Max	(A) $\times 2$ Typical	(A) $\times 3$ Typical
TGIB5022-100M	10.0	18.0	21.6	11.5	5.43
TGIB5022-120M	12.0	22.0	26.4	10.5	4.91
TGIB5022-150M	15.0	23.8	28.6	9.50	4.72
TGIB5022-180M	18.0	27.8	33.4	8.50	4.37
TGIB5022-220M	22.0	36.0	43.2	8.00	3.84
TGIB5022-270M	27.0	41.0	49.2	7.30	3.59
TGIB5022-330M	33.0	51.8	62.2	6.50	3.20
TGIB5022-390M	39.0	58.0	69.6	6.10	3.02
TGIB5022-470M	47.0	73.5	88.2	5.50	2.68
TGIB5022-560M	56.0	85.0	102	5.10	2.50
TGIB5022-680M	68.0	97.0	116	4.60	2.34
TGIB5022-820M	82.0	108	130	4.20	2.21
TGIB5022-101M	100	145	174	3.80	1.92
TGIB5022-121M	120	165	198	3.30	1.80
TGIB5022-151M	150	204	245	3.00	1.61
TGIB5022-181M	180	250	300	2.70	1.46
TGIB5022-221M	220	295	354	2.50	1.34
TGIB5022-271M	270	361	433	2.30	1.21
TGIB5022-331M	330	453	544	2.10	1.08
TGIB5022-391M	390	518	622	1.90	1.01
TGIB5022-471M	470	631	757	1.75	0.92
TGIB5022-561M	560	760	912	1.60	0.83
TGIB5022-681M	680	950	1,140	1.45	0.75
TGIB5022-821M	820	1,100	1,320	1.30	0.69
TGIB5022-102M	1,000	1,380	1,656	1.20	0.62
TGIB5022-152M	1,500	1,900	2,280	0.95	0.53
TGIB5022-222M	2,200	2,830	3,396	0.80	0.43


2 Product Dimensions (mm)










All data is tested on 25°C ambient temperature

1. Inductance measure condition at 1.00kHz,0.25V
2. Isat:the actual value of DC current when the Inductance decrease 20% of its initial value
3. Irms:the actual value of DC current when the the temperature rise is $\Delta T 40^{\circ}\text{C}$ ($T_a=25^{\circ}\text{C}$)


3 Saturation Current vs Temperature Rise Current Curve






4 Packing Specification

4.1 Carrier Tape Dimensions (mm)



※ Packing is referred to the international standard IEC 60286-3.

4.2 Reel Dimensions (mm)




4.3 Carton Dimensions and Packing Quantity

- Inner Carton: 365×345×105mm
- Out Carton : 385×365×245mm

Product Series	Quantity / Reel	Inner Carton Quantity	Out Carton Quantity
TGIB5022	400pcs	(400×2) = 800pcs	(800×2) = 1600pcs

5 Soldering Specification

5.1 Reflow Profile for SMT Components



5.2 Classification of Peak Package Body Temperature (Tp)

	Package Thickness	Package Volume		
		<350 mm ³	350~2000 mm ³	>2000 mm ³
PB-Free Assembly	<1.6mm	260°C	260°C	260°C
	1.6~2.5mm	260°C	250°C	245°C
	≥2.5mm	250°C	245°C	245°C

※ Reflow is referred to standard IPC/JEDEC J-STD-020D.

6 Notice of Use

- 6.1 Special remind:Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.
- 6.2 Product in packing storage condition:temperature 5~40°C, RH≤70%.
If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.
- 6.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- 6.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.
- 6.5 Always handle products with care.
- 6.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering.
Always ensure optimum conditions for soldering.
- 6.7 When this product will be used on a similar or new project to the original one, sometimes it might be unable to satisfy the specifications due to different condition of usage.
- 6.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devices or protection circuit in the end product.
- 6.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.
- 6.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.
- 6.11 Refrain from rinsing coils. If necessary, please consult with us.